

NOTICE - WHEN GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE UNITED STATES GOVERNMENT THEREBY INCURS NO RESPONSIBILITY NOR ANY OBLIGATION WHATSOEVER, AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY IN ANY WAY BE RELATED THERETO.

APPLICATION		REVISION HISTORY					
NEXT ASSY	USED ON	PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

### NASA KSC Export Control Office (ECO) Export/SBU Determination Record

EDDR# 1311341

**DOCUMENT INFORMATION:** (TITLE, NUMBER, REV, DATE)  
K0000146599-SPC  
Flexible Hose Specification, Vacuum Jacketed, LO2 Service

**SENSITIVE BUT UNCLASSIFIED (SBU)**

INSTRUCTIONS: This item must be reviewed under the requirements for "Sensitive But Unclassified Information" as described in NPR 1600.1, Chapter 5.

<http://nodis-dms.gsfc.nasa.gov>

	Yes	No	SBU Reviewer's Signature	Date	Company / Org
Document contains SBU?	<input type="checkbox"/>	<input checked="" type="checkbox"/>	 Heather White (affiliate) (4/25/2013)	04/25/2013	ESC

**EXPORT CONTROL (EC)**

INSTRUCTIONS: Attach the document requiring an export determination. Contact the KSC ECO Help Desk (867-9209) for help in completing this form.

<http://exportcontrol.ksc.nasa.gov/>


Contractor EC Reviewer's Name and Organization	Contractor EC Reviewer's Signature	Date
Heather White, ESC	 Heather White (affiliate) (4/25/2013)	04/25/2013

NASA ECO Reviewer's Name and Organization	NASA ECO Reviewer's Signature	Date

	EXPORT DETERMINATION (Check one box only)	
<b>EAR 99</b>	<input checked="" type="checkbox"/>	The information contained in the document is technical in content, but is not technical data as defined by the ITAR or the EAR, and therefore is EAR 99 NLR (no export license required). [General Prohibition S1k (Embargo) applies to all items subject to the EAR, i.e. items on the CCL and within EAR 99 NLR. You may not make an export or re-export contrary to the provisions of part 746 (Embargos and Other Special Controls) of the EAR and 22 CFR part 126.1 of the ITAR.]
<b>EAR Controlled</b>	<input type="checkbox"/>	This document is within the purview of the Export Administration Regulations (EAR), 15 CFR 730-774, and is export controlled. It may not be transferred to foreign nationals in the U.S. or abroad without specific approval of a knowledgeable NASA export control official, and/or unless an export license or license exemption is obtained/available from the Bureau of Industry and Security, United States Department of Commerce. Violators of these regulations are punishable by fine, imprisonment, or both.
<b>ITAR Controlled</b>	<input type="checkbox"/>	This document contains information which falls under the purview of the U.S. Munitions List (USML), as defined in the International Traffic in Arms Regulations (ITAR), 22 CFR 120-130, and is export controlled. It shall not be transferred to foreign nationals, in the U.S. or abroad, without specific approval of a knowledgeable NASA export control official, and/or unless an export license or license exemption is obtained/available from the United States Department of State. Violators of these regulations are punishable by fine, imprisonment, or both.

KSC FORM 7-657V2 NS (REV. 09/11) PREVIOUS EDITIONS ARE OBSOLETE

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN INCHES.  
INTERPRET DIMENSIONS AND  
TOLERANCES PER ASME Y14.5M-1994.  
TOLERANCES NO:  
FRACTIONS      DECIMALS      ANGLES



CAD MAINTAINED. CHANGES SHALL BE INCORPORATED ONLY BY THE DESIGN ACTIVITY	ORIGINAL DATE OF DRAWING (YY/MM/DD) 06/11/2013	<b>JOHN F. KENNEDY SPACE CENTER, NASA KENNEDY SPACE CENTER, FLORIDA</b>  <b>ICPSU FLEXIBLE HOSE SPECIFICATION, VACUUM JACKETED, LO2 SERVICE</b>			
	DRAFTER C. Exline				
SOFTWARE	ENGINEER S. Larsen	CHECKER	<b>SIZE    CAGE CODE    DWG NO    REV</b> <b>A      22264      K0000146599-SPC    -</b>		
FILENAME	ENGINEER S. Hoyle	STRESS			
MATERIAL	ENGINEER E. Thompson				
HEAT TREATMENT	SUBMITTED T. Adams	SCALE    None	UNIT WEIGHT    —	SHEET    1	OF    22
FINAL PROTECTIVE FINISH	APPROVED A. Littlefield				

KSC FORM 21-2C NS (REV 06/04) PREVIOUS EDITIONS ARE OBSOLETE

K0000146599-SPC, -.13, RELEASED, Verify Latest Revision in KDDMS

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

**CONTENTS**

**Contents**

1.	SCOPE.....	5
2.	APPLICABLE DOCUMENTS .....	5
2.1	Governmental .....	5
2.2	STANDARDS .....	6
2.3	Non-Governmental .....	6
3.	REQUIREMENTS .....	8
3.1	Definition.....	8
3.2	General .....	9
3.2.1	Fluid Service.....	9
3.2.2	Temperature and Pressure .....	9
3.2.3	Material Properties .....	9
3.2.4	Heat Leak .....	10
3.2.5	Bend Radius .....	10
3.2.6	Inner Flexible hose Assembly .....	11
3.2.7	Outer Flexible hose Assembly .....	12
3.2.8	VJ Joint Connections.....	12
3.2.9	Weld Fittings .....	13
3.2.10	Thermal Life Cycle .....	13
3.2.11	Listed / Unlisted Components Usage .....	13
3.3	Construction .....	14
3.3.1	General .....	14
3.3.2	Welder Qualification .....	14
3.3.3	Non Destructive Evaluation (NDE) Examiners .....	14
3.3.4	Non Destructive Evaluation (NDE).....	14
3.3.5	Welding .....	15
3.3.6	Low Temperature Toughness.....	15
3.3.7	Passivation.....	15
3.3.8	Cleaning.....	15
3.3.9	Name Plates and Product Marking.....	15
3.3.10	Workmanship .....	16
3.3.11	Interchangeability.....	16
3.3.12	Safety .....	16
3.3.13	Human-Factors Engineering.....	16
3.3.14	Security.....	17
3.3.15	Government-Furnished Property .....	17
3.4	Documentation .....	17

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT —	SHEET 2 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

3.5	Logistics .....	17
3.6	Personnel and Training.....	17
3.7	Major-Component Characteristics .....	17
3.8	Precedence.....	17
4.	VERIFICATION .....	17
4.1	Responsibility for Inspection.....	17
4.2	Special Tests and Inspections.....	18
4.3	Verification Inspections .....	18
4.3.1	Required Testing Chronology .....	18
4.3.2	Cold Shock .....	18
4.3.3	Pressure/Leak Testing .....	19
4.3.4	Mass Spectrometer Leak Testing .....	19
4.3.5	Vacuum Retention Test .....	19
4.3.6	Dimensional Verification .....	20
4.3.7	Responsibility For Verification / Inspection .....	20
5.	PREPARATION FOR DELIVERY.....	21
5.1	Preservation .....	21
5.1.1	Protective covers .....	21
5.1.2	Packaged per KSC-C-123 .....	21
5.1.3	Vacuum in Annulus.....	21
5.1.4	Inner Line Pressure.....	21
5.1.5	Recordings.....	21
5.2	Packing .....	22
6.	NOTES .....	22
6.1	Intended Use.....	22

**LIST OF TABLES**

Table 1: Minimum Flexible Hose Center-Line Bend Radius.....	10
---	----

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 3 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

**Abbreviations, acronyms, and symbols**

- ASME      American Society of Mechanical Engineers
- DP        Design Pressure
- GN<sub>2</sub>     Gaseous Nitrogen
- GO<sub>2</sub>     Gaseous Oxygen
- GSE      Ground Support Equipment
- KSC      Kennedy Space Center
- LO<sub>2</sub>     Liquid Oxygen
- LN<sub>2</sub>     Liquid Nitrogen
- NASA     National Aeronautics and Space Administration
- NDE      Non-Destructive Evaluation
- NPS      Nominal Pipe Size
- VJ        Vacuum Jacket

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 4 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

## 1. SCOPE

This specification provides technical information for the design, fabrication, and testing of vacuum jacketed flexible hose assemblies used in the transfer of liquid oxygen (LO<sub>2</sub>), gaseous oxygen (GO<sub>2</sub>) and liquid nitrogen (LN<sub>2</sub>).

## 2. APPLICABLE DOCUMENTS

The following documents form a part of this document to the extent specified herein. The latest revision applies unless a specific revision is indicated. However, when this document is used for procurement, including solicitations, or is added to an existing contract, the specific revision levels, amendments, and approval dates of said documents shall be specified in an attachment to the Solicitation/Statement of Work/Contract.

In case of conflict between referenced document and this specification, this specification shall take precedence

### 2.1 Governmental

#### National Aeronautics and Space Administration (NASA)

NASA-SPEC-5004      Welding of Aerospace Ground Support Equipment and Related Nonconventional Facilities

#### NASA/Kennedy Space Center

KSC-C-123      Surface Cleanliness of Fluid Systems, Specification For

#### Military Specifications

MIL-PRF-27407C      Propellant Pressurizing Agent, Helium

MIL-PRF-27401F      Propellant Pressurizing Agent, Nitrogen

#### KSC Drawings

79K14672      Vacuum Pump out ports

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT —	SHEET 5 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

**2.2 STANDARDS**

Copies of specifications, standards, drawings, and publications required by vendors in connection with specified procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.

**2.3 Non-Governmental**

The American Society of Mechanical Engineers

- ASME B31.3                      Process Piping
- ASME B16.5                    Pipe Flanges and Flanged Fittings
- ASME B16.9                    Factory-Made Wrought Butt welding Fittings

American Society of Nondestructive Testing (ASNT)

- ASNT-TC-1A                    Recommended Practice, Personnel Qualification and Certification in Nondestructive Testing

American Society of Testing and Materials

- ASTM A182                      Standard Specification for Forged or Rolled Alloy and Stainless Steel Pipe Flanges, Forged Fittings, and Valves and Parts for High Temperature Service
- ASTM A193                      Standard specification for alloy-steel and stainless steel bolting for high temperature or high pressure service and other special purpose applications.
- ASTM A194                      Standard specification for carbon and alloy steel nuts for bolts for high pressure or high temperature service, or both
- ASTM A240                      Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Applications
- ASTM A312                      Standard Specification for Seamless, Welded, and Heavily Cold Worked Austenitic Stainless Steel Pipes

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 6 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

ASTM A320                      Standard specification for alloy-steel and stainless steel bolting materials for low temperature service

ASTM A403                      Standard Specification for Wrought Austenitic Stainless Steel Piping Fittings

ASTM B575                      Standard Specification for Low-Carbon Nickel-Chromium-Molybdenum, Low-Carbon Nickel-Chromium-Molybdenum-Copper, Low-Carbon Nickel-Chromium-Molybdenum-Tantalum, and Low-Carbon Nickel-Chromium-Molybdenum-Tungsten Alloy Plate, Sheet, and Strip

ASTM A580                      Standard Specification for Stainless Steel Wire

ASTM A967                      Standard Specification for Chemical Passivation Treatments for Stainless Steel Parts

National Bureau of Standards

NBS Monograph 29                      Thermal Expansion of Technical Solids at Low Temperatures. A Compilation from the literature

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT —	SHEET 7 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

### 3. REQUIREMENTS

#### 3.1 Definition

The assemblies are vacuum jacketed flexible hose(s) used to deliver cryogenics commodity (LO<sub>2</sub>, GO<sub>2</sub>, LN<sub>2</sub>) as part of the Ground Support Equipment (GSE).

For the purpose of this document, the following definitions shall apply.

- a. **Annulus** – Space between inner and outer piping walls
- b. **Calendar Day** – Consecutive days on a calendar.
- c. **Field Monitor** – Pressure monitoring performed by individual from a dial indicator gage without electronic transmission.
- d. **shall:** - Used to indicate a requirement which must be implemented and its implementation verified;
- e. **should:** Used to indicate a goal which must be addressed by the design but is not formally verified;
- f. **Will:** Used to indicate a statement of fact and is not verified.
- g. **TBR** – to be resolved / reviewed, involves data / processes to be designed / developed by contractor and provided to NASA at 45 percent and 90 percent design reviews for approval.
- h. **TBD** – to be determined, involves data / processes in work at present by NASA, to be updated by NASA and incorporated to specification prior to contract award.
- i. **TBS** – to be supplied, involves data / process to be supplied by the contractor to NASA as part of deliverables of this specification, but are not required for approval by NASA.
- j. **Work Day** – Monday through Friday.

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 8 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

## 3.2 General

### 3.2.1 Fluid Service

- 3.2.1.1 The service shall be for Liquid Oxygen (LO<sub>2</sub>), Gaseous Oxygen (GO<sub>2</sub>), Gaseous Helium (GHe), Liquid Nitrogen (LN<sub>2</sub>) or Gaseous Nitrogen (GN<sub>2</sub>)
- 3.2.1.2 All flexible hose assembly components shall be designed and fabricated as normal fluid service in accordance with ASME B31.3.
- 3.2.1.3 Examination processes and Pass/Fail criteria shall be in accordance with severe cyclic service requirements in ASM E B31.3.

### 3.2.2 Temperature and Pressure

- 3.2.2.1 The lowest ambient temperature expected in service shall be +20F.
- 3.2.2.2 The nominal ambient temperature for ground operations shall be +80 degrees F
- 3.2.2.3 The maximum ambient temperature in service shall be +105 degrees F.
- 3.2.2.4 The assembled flexible hose shall be designed for -321 degrees F to +158 degrees F at 285 psig.
- 3.2.2.5 The Design Pressure (DP) for the inner flexible hose shall be 300 PSIG with atmospheric pressure applied to external surface of inner line.
- 3.2.2.6 The Design Pressure (DP) for the inner flexible hose shall be 285 PSIG with 0 psia (full vacuum) applied to external surface of inner line (annular space).
- 3.2.2.7 The outer jacket flexible hose shall have an annular space design pressure (as defined by ASME B31.3) of 35 psig @ 158 degrees F.
- 3.2.2.8 The outer jacket shall be designed for external pressure of 20 psig (above ambient) with 0 psia (full vacuum) annular space pressure.

### 3.2.3 Material Properties

- 3.2.3.1 All materials used as pressure components shall meet the requirements of ASME 31.3.
- 3.2.3.2 Thermal properties of materials at cryogenic temperatures shall be as described from the National Bureau of Standards - Thermal Expansion of Technical Solids at Low Temperatures. A Compilation from the literature, NBS Monograph 29.

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 9 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

3.2.3.3 All materials for construction are specified in this specification. However, the contractor may use materials not specifically called out in this specification provided that chemical and mechanical analysis for the material are submitted to the owner for approval prior to start of fabrication. All materials including those in the vacuum annulus space shall be compatible with the fluid service.

**3.2.4 Heat Leak**

3.2.4.1 The maximum heat leak for the vacuum jacketed flexible hose, including spacers but not end fittings, at LO<sub>2</sub> cryogenic conditions and an ambient temperature of 80 degrees F shall be (determined by test or analysis at the maximum ambient temperature):

<u>Nominal ID of Inner Line (in)</u>	<u>Btu/hr/foot</u>
3x5	2.52
4x6	3.03

**3.2.5 Bend Radius**

3.2.5.1 The bend radius shall be as specified in **Table 1**.

<b>Minimum Center-Line Bend Radius</b>		
<b>VJ Flex Hose Size (inner x outer wall - NPS)</b>	<b>Dynamic Flexing (inches)</b>	<b>Static Bend (inches)</b>
3"x5"	28	12.8
4"x6"	32	14.8

**Table 1: Minimum Flexible Hose Center-Line Bend Radius**

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 10 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

### 3.2.6 Inner Flexible hose Assembly

- 3.2.6.1 Inner pipe shall be constructed of dual grade A 312 TP304/304L, or dual grade A312 TP316/TP316L. For these dual grade steels, the design shall be based on the allowable stresses tabulated in ASME B31.3 for the straight grade. A312 TP304L or TP316L pipe shall not be used
- 3.2.6.2 Inner pipe shall be schedule 10.
- 3.2.6.3 Inner flexible hose shall be closed pitch annular convolutions using stainless steel ASTM A240 dual grade 304/304L, or dual grade 316/316L. When using stainless steel materials that meet ASTM requirements for two grades, the design may be based on the allowable stresses tabulated in ASME B31.3, Table A-1 for the straight grade
- 3.2.6.4 Compression length shall be designed to include braid tension required for full engagement of convolutes with vacuum in outer annulus, inner hose at minimum design temperature, and 0 psig in inner hose.
- 3.2.6.5 Length of hose shall be controlled by the inner line braid. The inner line braid shall be installed so that the inner line convoluted section is compressed a sufficient amount to maintain the inner line braid in tension and prevent any reduction in length of the line when the vacuum annulus is evacuated
- 3.2.6.6 The inner line shall be supported with spacers that center it within the outer jacket. The design, location, and material of the spacers are left to the vendor to decide.
- 3.2.6.6.1 Details of the design and material selection shall be submitted to the owner for approval prior to fabrication.
- 3.2.6.7 Spacers shall allow for motion of the convolutes. Spacers shall not be located within 3/4" of a circumferential hose weld
- 3.2.6.8 If a multi-layer insulation (MLI) system is utilized to meet heat leak requirements, the MLI shall consist of aluminum foil and a microfiber insulating sheet.
- 3.2.6.9 Aluminized Mylar shall not to be used.
- 3.2.6.10 Each vacuum jacket annulus space shall be equipped with a chemical gettering system consisting of desiccant, molecular sieve, and hydrogen converter.
- 3.2.6.11 Inner flexible hose primary welds should accommodate 100% radiography.
- 3.2.6.11.1 If inner flexible hose primary weld cannot accommodate 100% radiography, the inner flexible hose primary welds shall accommodate dye penetrant testing.

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 11 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

### 3.2.7 Outer Flexible hose Assembly

- 3.2.7.1 Outer pipe shall be constructed of dual grade A 312 TP304/304L, or dual grade A312 TP316/TP316L. For these dual grade steels, the design shall be based on the allowable stresses tabulated in ASME B31.3 for the straight grade. A312 TP304L or TP316L pipe shall not be used
- 3.2.7.2 Outer pipe shall be schedule 10.
- 3.2.7.3 The outer vacuum jacket shall be closed pitch annular convolution using ASTM B575 N06022 (Hastelloy C22).
- 3.2.7.4 The outer line convolutions shall be covered with braided wire reinforcement per ASTM A580 316/316L (dual grade) stainless steel.
- 3.2.7.5 Compression length shall be designed to include braid tension required for full engagement of convolutes with vacuum in outer annulus, inner hose at minimum design temperature, and 0 psig in inner hose.
- 3.2.7.6 The outer flexible hose welds shall accommodate 100% dye penetrant examination per ASME B31.3
- 3.2.7.7 The outer line braid shall be installed so that all axial loads are transmitted through the inner line braid.
- 3.2.7.8 **Vacuum Valve**
- 3.2.7.8.1 Each section of vacuum jacketed flexible hose shall be equipped with a vacuum valve assembly that contains an evacuation port and a relief valve in accordance with 79K14672-3. Vacuum valve height dimension shown on deliverables list drawings are for reference only.

### 3.2.8 VJ Joint Connections

- 3.2.8.1 Male bayonet shall be welded to flexible hose pipe stub.
- 3.2.8.2 Male Bayonet with flange connections will be Government Furnished Equipment (GFE)
- 3.2.8.3 Fastener bolt, washer and nut materials will be Government Furnished Equipment (GFE)
- 3.2.8.4 Male Bayonet shipping covers will be Government Furnished Equipment (GFE)
- 3.2.8.5 Butt welded joint designs shall meet the requirements of ASME B16.9.

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 12 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

3.2.8.6 Butt welded end designs shall meet the requirements of ASME B16.25

3.2.8.7 Gasket size, material, type and part number shall be specified and provided to owner.

### 3.2.9 Weld Fittings

3.2.9.1 Fittings shall be as per ASME B16.9 and ASTM A403 class WP-S (seamless) or WP-WX (welded with 100% x-ray) and shall be WP316/WP316L (dual graded) and shall be of schedule to match flexible hose segment.

### 3.2.10 Thermal Life Cycle

3.2.10.1 The flexible hose assemblies shall have a designed thermal cycle life of a minimum of 3,000 cycles. A thermal cycle is defined as the flexible hose assembly starting at ambient temperature, then being taken down to minus 321 degrees F, held at that temperature for a minimum of 15 minutes, and then allowed to return to ambient temperature. A pressure cycle for the assembled VJ pipe shall be 0 psig to 285 psig and back to 0 psig. These requirements are design requirements only and do not require verification by test.

### 3.2.11 Listed / Unlisted Components Usage

3.2.11.1 The flexible hose assembly shall be qualified in accordance with ASME B31.3 paragraph 304.7.2 (c) or (d). Paragraph 304.7.2(e) of ASME B31.3 shall not be utilized to qualify the flexible hose.

SIZE	CAGE CODE	DWG NO	REV
<b>A</b>	22264	<b>K0000146599-SPC</b>	-
SCALE	UNIT WEIGHT	SHEET	OF
None	—	13	22

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

### 3.3 Construction

#### 3.3.1 General

3.3.1.1 All work on vacuum jacketed flexible hose assemblies which exposes the annular area between the inner and outer line shall be performed in a controlled environment which will minimize the exposure to moist air, oil, grease or other contaminants. A dry GN<sub>2</sub> purge shall be maintained whenever possible, after annulus closure. The annulus area of the vacuum jacketed lines shall be maintained clean at all times. Application of tape, grease pencil, and chalk marks shall be avoided. Exposed surface areas shall be thoroughly degreased before the annulus is closed.

#### 3.3.2 Welder Qualification

3.3.2.1 All welding shall be performed by qualified welders per weld procedure specifications for each weld in accordance with NASA-SPEC-5004 and ASME B31.3. Weld traceability maps of welder and procedure number at each joint are required for each flexible hose.

#### 3.3.3 Non Destructive Evaluation (NDE) Examiners

3.3.3.1 Weld examiners shall be qualified in accordance with NASA-SPEC-5004, ASME B31.3 paragraph 342 and ASNT-TC-1A Level III.

#### 3.3.4 Non Destructive Evaluation (NDE)

3.3.4.1 All welding inspections shall be performed in accordance with NASA-SPEC-5004 and ASME B31.3 by qualified weld examiners.

3.3.4.2 Weld examination pass/fail criteria shall be per ASME B31.3 severe cyclic service.

3.3.4.3 All welds shall be 100% examined per NASA-SPEC-5004 and ASME B31.3 as follows:

3.3.4.3.1 All welds shall be visually examined.

3.3.4.3.2 All welds located on outer jacket shall be dye penetrant examined

3.3.4.3.3 All welds located on outer flexible hose shall be dye penetrant examined

3.3.4.3.4 All welds located on inner flexible hose shall be radiographed. Radiograph exception per 3.3.4.4.

3.3.4.3.5 All longitudinal seam welds shall be radiographed.

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT —	SHEET 14 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

3.3.4.4 If welds located on inner flexible hose cannot be radiographed due to the inherent design of the flexible hose, all welds shall be 100% dye penetrant tested. Pass/Fail criteria shall be per ASME B31.3 for severe cyclic service. Dye penetrant shall be removed from the annular space in order to meet the vacuum retention requirements of this specification.

3.3.4.5 Dye penetrant will be removed from the annular space in order to meet the vacuum retention requirements of this specification.

3.3.4.6 Seams on convoluted sections shall be 100% radiographed prior to the forming process. Pass/fail criteria shall be per ASME B31.3 for severe cyclic criteria.

### 3.3.5 Welding

3.3.5.1 All welds should be full penetration welds in accordance with NASA-SPEC-5004 and ASME B31.3. If full penetration welds are not possible due to the inherent design, single sided fillet welds may be used.

3.3.5.2 Backing rings shall not be used.

3.3.5.3 Brazed and brazed welded joints shall not be used.

3.3.5.4 Remove scale, burrs and break sharp edges

3.3.5.5 Pull braids tight to ensure contact with all convolutes after bellows compression and prior to welding braid in ferrule.

### 3.3.6 Low Temperature Toughness

3.3.6.1 All welds shall meet the requirements for low temperature toughness (impact test) in accordance with ASME B31.3, paragraph 323.2.2.

### 3.3.7 Passivation

3.3.7.1 Welds and heat affected areas shall be passivated per ASTM A967. Passivation chemicals/fluid/materials shall be removed from the annular space in order to meet the vacuum retention requirements of this specification.

### 3.3.8 Cleaning

3.3.8.1 The inner surfaces of all flexible hose assemblies and components shall be cleaned to KSC-C-123, level 300A. All cleaning processes and cleanliness level inspections shall be as specified in KSC-C-123.

### 3.3.9 Name Plates and Product Marking

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 15	OF 22

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

Electrochemical Etch (Type II), Engrave (Type VII), or Laser Engrave (Type VIII) flexible hose/part using 0.125 inch minimum characters per provisions in MIL-STD-792. At a minimum, the data indicated below shall be included:

At a minimum, the data indicated below shall be included:

- manufacturing vendor's name
- Contract Number
- KSC Drawing Number
- KSC Spool number
- Serial Number
- Design Pressure
- Test pressure
- Test date
- Service
- Year Built
- Temperature Range
- Weight

### 3.3.10 Workmanship

Hardware shall be fabricated and finished so appearance, fit, and adherence to specified dimensions and tolerances are observed and in a manner that ensures reliable operations in accordance with the requirements specified herein. Particular attention shall be given to the neatness and thoroughness of construction and to the freedom of parts from burrs and sharp edges that might damage associated equipment or cause injury to personnel. Any item failing the acceptance criteria shall be repaired or replaced and reexamined by the same acceptance criteria as required for the original work.

### 3.3.11 Interchangeability

Hardware assemblies, components, and parts with the same part number shall be physically and functionally interchangeable

### 3.3.12 Safety

N/A

### 3.3.13 Human-Factors Engineering

N/A

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT —	SHEET 16	OF 22

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

**3.3.14 Security**

N/A

**3.3.15 Government-Furnished Property**

N/A

**3.4 Documentation**

N/A

**3.5 Logistics**

N/A

**3.6 Personnel and Training**

N/A

**3.7 Major-Component Characteristics**

N/A

**3.8 Precedence**

In case of conflict between referenced document and this specification, this specification shall take precedence.

**4. VERIFICATION**

**4.1 Responsibility for Inspection**

Unless otherwise specified in the contract or order, the vendor shall be responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the vendor may use his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT —	SHEET 17 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

## 4.2 Special Tests and Inspections

### 4.2.1.1 Flexible Hose Measurements

- 4.2.1.1.1 Measure and record the weight of flexible hose +/- 5 pounds.
- 4.2.1.1.2 Measure the length of the flexible hose under the following conditions:
- 4.2.1.1.3 Ambient pressure and temperature with the annulus evacuated below 50 um Hg
- 4.2.1.1.4 Measure the length of the hose in the straight position
- 4.2.1.1.5 Vendor shall provide to the owner convolute dimensions including but not limited to pitch, material thickness, convolute height, minimum inside dimension between bottom of convolutes.

## 4.3 Verification Inspections

Testing commodities shall conform to specifications as follows:

- Gaseous helium to MIL-PRF-27407C, Type I, Grade A
- Gaseous nitrogen to MIL-PRF-27401F, Type I, Grade B
- Liquid nitrogen to MIL-PRF-27401F, Type II, Grade B

### 4.3.1 Required Testing Chronology

The testing in sections 4.3.2 to 4.3.6 shall be performed sequentially.

### 4.3.2 Cold Shock

- 4.3.2.1 The completed vacuum jacketed flexible hose will have the vacuum annulus evacuated to a minimum of 10 microns of Hg pressure.
- 4.3.2.2 The assembly shall be cold shocked with LN<sub>2</sub> by tilting the line at least 15 degrees and introducing the LN<sub>2</sub> into the assembly at the low end, allowing the boil off gas to vent from the high end. The chilldown and tilting of the assembly shall continue until a steady stream of LN<sub>2</sub> is forced out the high end. The LN<sub>2</sub> supply shall then be maintained to keep LN<sub>2</sub> within 6 inches, at the farthest point, from the end of the spool, and allowing the assembly to cold-soak for 1 hour
- 4.3.2.3 .The vacuum readings shall be recorded before, during, and after the cold shock test. The vacuum reading after the cold-shock test shall be taken when the assembly returns to ambient temperature. Post cold shock vacuum reading shall be less than 50 microns of Hg pressure

SIZE	CAGE CODE	DWG NO	REV
A	22264	K0000146599-SPC	-
SCALE	None	UNIT WEIGHT	SHEET 18 OF 22

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

### 4.3.3 Pressure/Leak Testing

- 4.3.3.1 The pressure test shall be conducted via hydrostatic testing at a minimum of 150% or pneumatic leak test at 110% of the design pressure at coincident temperature in accordance with ASME B31.3.
- 4.3.3.2 The pressure shall be maintained for a minimum of 10 minutes. The vacuum readings shall be recorded prior to test and after the pressure has been reduced to DP and at end of test where pressure is less than 10 psig. The vacuum jacketed flexible hose undergoing test shall exhibit no leakage while undergoing leak testing and show no permanent deformation or damage as result of the leak testing.
- 4.3.3.3 Leak test of the outer jacket (by pressurizing the annular space) is not required.
- 4.3.3.4 Leak testing shall be performed at ambient temperature.

### 4.3.4 Mass Spectrometer Leak Testing

- 4.3.4.1 The vacuum jacket annulus shall be evacuated to a minimum of 10 microns of Hg pressure.
- 4.3.4.2 One of the following two testing procedures shall be used. Do not introduce helium into the vacuum annulus for any testing.
- 4.3.4.2.1 With inner line pressurized to MDP with 100% helium and holding at MDP for 1 minute minimum, the mass spectrometer leakage indication shall be below  $10^{-7}$  std-cc/sec. To accomplish this test, a mass spectrometer set capable of sensitivity to  $10^{-9}$  std-cc/sec shall be used.
- 4.3.4.2.2 As an option with inner line pressurized to MDP with 10% helium/90% nitrogen and holding at MDP for 1 minute minimum, the mass spectrometer leakage indication shall be below  $10^{-9}$  std-cc/sec. To accomplish this test, a mass spectrometer set capable of sensitivity to  $10^{-10}$  std-cc/sec shall be used.
- 4.3.4.3 The outer jacket shall be tested with all jacket welds surrounded by a 100% GHe atmosphere.
- 4.3.4.3.1 GHe leakage shall be less than  $10^{-7}$  std-cc/sec using a Helium Mass Spectrometer Leak Detector set to a minimum sensitivity of  $10^{-9}$  scc/s

### 4.3.5 Vacuum Retention Test

- 4.3.5.1 Each section of the vacuum jacketed flexible hose outer vacuum jacket shall be evacuated to a minimum of 10 micrometers of Hg pressure at ambient temperature.

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT —	SHEET 19	OF 22

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

4.3.5.2 The vacuum level within each section of the outer vacuum jacket shall be measured and recorded every twenty-four (24) hours for a period of at least seven (7) days.

4.3.5.2.1 The final pressure at the end of the test period within each section of the vacuum jacket must stabilize at or below 50 microns of Hg pressure to be acceptable.

**4.3.6 Dimensional Verification**

4.3.6.1 Flexible hose assemblies shall be dimensionally verified to be in accordance with the vendor's fabrication drawings prior to packaging for shipment.

**4.3.7 Responsibility For Verification / Inspection**

4.3.7.1 The vendor shall be responsible for the performance of all verification (analysis, test, demo or inspection) requirements as specified herein. Except as otherwise specified, the vendor may use his own facilities or any commercial laboratory acceptable to NASA. NASA reserves the right to witness or perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.3.7.2 The Vendor shall formulate acceptance test procedures for all components and will provide the facility and instrumentation to perform all relevant tests to ensure compliance with this specification. The acceptance test procedures shall include but not be limited to all of the testing procedures specifically outlined in this document.

4.3.7.3 All items purchased or manufactured by a subcontractor used in the Vendor's work shall be clearly identified and tabulated.

4.3.7.4 All material and components shall be traceable to original vendor via material certification records.

4.3.7.5 NASA reserves the right to have access to the Vendor's facility at any time during the design, fabrication and code testing. NASA shall have the right to witness any manufacturing or testing procedures upon request. When requested, the Vendor shall provide a minimum of 7 days' notice in advance of any test date to allow for NASA (or its designated contractor representative) to make the necessary travel arrangements.

4.3.7.6 Review of analysis data and procedures by NASA shall not release the Vendor from its responsibility to correct errors, oversights and omissions to ensure conformance to the requirements in this document and ASME code requirements.

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 20 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

**5. PREPARATION FOR DELIVERY**

**5.1 Preservation**

5.1.1 Protective covers

5.1.1.1 The VJ flexible hoses shall be furnished with stainless steel protective end covers to prevent damage or contamination during storage, transportation and handling.

5.1.2 Packaged per KSC-C-123

5.1.2.1 All flexible hose assemblies shall be packaged per KSC-C-123. Packing design shall be approved by NASA prior to use.

5.1.3 Vacuum in Annulus

5.1.3.1 Vacuum levels at delivery to the owner shall be 50 microns of HG pressure or less

5.1.3.2 Annulus shall be sealed and maintained at vacuum levels from acceptance tests.

5.1.3.3 All flexible hose assembly vacuum levels shall be checked and recorded prior to shipment for validation at KSC receiving site prior to acceptance.

5.1.4 Inner Line Pressure

5.1.4.1 Cleanliness shall be maintained.

5.1.4.2 Seal inner pipe ends and ports with pressure retaining flanges equipped with pressure gage and gas charging tee (1 set per pipe assembly). All flanges shall meet the component requirements in Section 3.

5.1.4.3 Establish a minus 65F (24 ppm) or better dew point using 2 micron filtered MIL-PRF-27401F, Type II, Grade B GN<sub>2</sub> in accordance with Test Method III (A.3.3) of KSC-C-123 then establish a 5 +/-2 psig GN<sub>2</sub> blanket pressure

5.1.4.4 Capability shall be provided to field monitor blanket pressure, isolate pressure gage and re-establish any lost blanket pressure. All components and fittings shall be cleaned to fabricated component level or better

5.1.4.5 Leak check shall be performed on pressure ports using MSFC-SPEC-384 Type 1 or 2 leak check fluid. Verify no bubble formation for one minute minimum.

5.1.5 Recordings

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 21 OF 22	

REVISION HISTORY					
PART NO.	ZONE	REV	DESCRIPTION	DATE	APPROVAL

5.1.5.1 All flexible hose assembly vacuum levels shall be checked and recorded prior to shipment for validation at KSC receiving site prior to acceptance.

5.1.5.2 All flexible hose assembly GN2 blanket pressures shall be checked and recorded prior to shipment for validation at KSC receiving site prior to acceptance.

**5.2 Packing**

The vendor shall package each vacuum jacketed flexible hose section within a hard sided container (at a minimum wood construction) using standard commercial practice, ensuring each vacuum jacketed flexible hose section is protected against damage during shipment. Entire flexible hose section length must also be protected against damage using isolation / separation means between segments during shipment. Boxes shall be strong enough to support being picked up using a forklift and/or using lifting straps. The boxes should be capable of being stacked. Flexible hoses can be shipped on saddle supports with hold-downs, or equivalent means. More than one flexible hose may be contained in a box. The boxes do not need to be weatherproof. Shipping containers shall conform to freight classification rules and applicable container specifications. These shipping containers shall be capable of being picked-up by fork lift or lifting straps.

**6. NOTES**

**6.1 Intended Use**

This document is intended to establish the requirements for fabrication and testing of LO<sub>2</sub> vacuum jacketed flexible hose.

NOTICE. The Government drawings, specifications, and/or data are prepared for the official use by, or on behalf of, the United States Government. The Government neither warrants these Government drawings, specifications, or other data, nor assumes any responsibility or obligation, for their use for purposes other than the Government project for which they were prepared and/or provided by the Government, or any activity directly related thereto. The fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded, by implication or otherwise, as licensing in any manner the holder or any other person or corporation nor conveying the right or permission to manufacture, use, or sell any patented invention that may relate thereto.

Custodian:

NASA – John F. Kennedy Space Center  
Kennedy Space Center, Florida 32899

Preparing Activity:

John F. Kennedy Space Center

SIZE <b>A</b>	CAGE CODE 22264	DWG NO <b>K0000146599-SPC</b>	REV -
SCALE None	UNIT WEIGHT _	SHEET 22 OF 22	